



- The Ultra Noise cancelling Mic filters 90% background noise
- Broad Band audio frequency
- Option for MIC AGC control, improves the compatibility with different Systems
- Hearing protection with Active Protection TM technology
- 300° rotation MIC boom offers optimal convenience.
- Mirror decoration surface with Nano-plating technology
- (Auto Mute TM) function when boom rotates to 60°to -60° (option)

SPECIFICATIONS

1. Features			
Receiving Type	Dynamic moving coil	Connection type	Quick Link
Microphone	ECM	Microphone boom	300° adjustable ,Flex boom
Wearing Style	Adjustable headband	Comfort aid	Leather/Foam ear cushion
2. Mechanical Specifications			
Weight(without cable)	53g	Contacts	phosphor bronze gold-plated
Cord length	1.0m	Housing	PA66 Shell Injection
Insertion cycles	10000 minimum	Storage Temperature	-40℃~70℃
3. Electroacoustical Specifications			
Receiving			
Diameter ϕ	27 mm	THD @ 1kHz	<5%
Rated Frequency Range	Broadband(150Hz~6.8KHz)	Max in-band Distortion	<10%
Nominal Impedance	150 Ω ±15%	Sealed acoustic press limit @ 1Khz	Measured according to IEC. 318 Standard Audio Test
Sealed Sensitivity @ 1kHz	103±3dB		Measured according to VBeT subjective RX Audio Standard Test (HATS)
Transmitting			
Rated Frequency Range	100-10KHz	Noise canceling (below 1kHz, far field)	Noise cancelling
Directivity	Cardioid	Sensitivity @ 1kHz @ 1kHz (RL=2.2K Ω Vs=3.0V DC 0dB=1V/Pa)	-41±3 dB